



# The Terminator

The Reliable Controls® Network Accessory End Of Line Terminator (NA-EOL) optimizes communication between Reliable Controls® devices and devices from other manufacturers that are connected on a common EIA-485 network, using BACnet® or Modbus protocol.









## **End of Line Terminator**

## Tech Specs

#### **Supply Voltage**

• 10 VDC @ 10 mA to 24 VAC @ 0.24 VA

#### Dimensions

• 7.9 cm L x 4.3 cm W x 2.3 cm H (3  $^{1}/_{8}$  " L x 1  $^{11}/_{16}$  " W x  $^{15}/_{16}$  " H)

#### Mounting

• 2 x #8 screws 3 cm (1 <sup>3</sup>/<sub>16</sub>")

### Weight

35.0 g (1.2 oz.)

## Ambient Limits

- Operating: -20 °C to 55 °C (-4 °F to 131 °F)
- Shipping: -20 °C to 60 °C (-4 °F to 140 °F)
- Humidity: 10% to 90%
- RH non-condensing

## **Features**

#### **Biased Terminator**

• Thevenin equivalent impedance of 108  $\Omega$ 

#### **Functional Design**

- Robust plastic case
- Mounting screws included

#### Power

- Flexible input power 10 VDC to 24 VAC
- Over-voltage and transient protection
- Power status LED

## Warranty

• 5 years

## **Ordering**

#### **NA-EOL**

 Network Accessory End of Line<sup>™</sup>

## APPLICATION DIAGRAM

