



MACH-ProAir™
BACnet® Controller

Versatile VAV

Engineered to exceed the specifications for a wide variety of Variable Air Volume (VAV) applications, the Reliable Controls® MACH-ProAir™ is a fully programmable BACnet Building Controller (B-BC) with numerous downloadable standard codes and flexible I/O options, all priced to meet a modest budget.



5 year
Warranty

Better by design



www.reliablecontrols.com/MPA

* UL® and CE® pending

TECH SPECS

Processor & Memory

- 66 MHz, high-performance, 32-bit embedded microcontroller with onboard Flash memory
- Controller database, values, log data, and configuration held in robust non-volatile memory
- Operating System firmware easily updated at any time over the network

Supply Voltages

- 24 VAC $\pm 10\%$ 32 VA max. 50/60 Hz
 - 24 VDC $\pm 10\%$ 12 W max.
- Note: MPA-12 requires 24 VAC only to support internal power to TRIACS

Communications

- MS/TP
 - EIA-485 @ 76.8 Kbps max.
 - Auto-baud detection
- SMART-Net™
 - 4 SMART-Sensors™ max.
 - RJ-11 port on all models
 - 4 wire terminal connector on all models

Universal Inputs

- 12-bit A/D converter
- Soft selectable: 0–10 VDC, 4–20 mA, thermistor/dry contact
- Impedance:
 - 3M Ω on 0–10 VDC range
 - 250 Ω on 4–20 mA range
 - 20k Ω on thermistor range
- 40 Hz pulse counting (supports flow meters)
- 24 VAC over-voltage protection

Universal Outputs

- 10-bit D/A converter
- Analog: 0–12 VDC
- Binary: 0/12 VDC
- Output power: 75 mA @ 12 VDC
- 24 VAC over-voltage and short protection

TRIAC Outputs

- 24 VAC @ 0.5 A

SETUP-Tool™

- SETUP-Tool™ optional for MS/TP configuration

Dimensions

- With actuator:
 - 22.7 cm L x 10.1 cm W x 7.6 cm H (8 15/16" L x 3 15/16" W x 3" H)
- Without actuator:
 - 19.9 cm L x 10.1 cm W x 7.6 cm H (7 13/16" L x 3 15/16" W x 3" H)
- With MPA-C:
 - 22.7 cm L x 15.0 cm W x 7.6 cm H (8 15/16" L x 5 7/8" W x 3" H)

Mounting

- Supplied with #8 screw
- Compatible with 3/8" to 1/2" damper blade shaft

Weight

- 0.7 kg (1.8 lb.)

Ambient Limits

- Operating: 0 °C to 50 °C (32 °F to 122 °F)
- Shipping: -40 °C to 60 °C (-40 °F to 140 °F)
- Humidity: 10% to 90% RH non-condensing

Features

Dynamic Database

- Shared memory allows creation of supported objects as required (up to memory max, or 128 object limit, whichever is reached first)
- All models provide 32K of database memory and 28K of trend memory
- Typical Object Configuration table shown on next page

Protocol

- BACnet®
 - MS/TP (EIA-485)

Motor Control

- Standard VAV and optimized motor control algorithms stored in firmware
- Numerous standard application codes can be downloaded from the Reliable Controls® website
- Optional user-programmed algorithm

Engineered Enhancements

- Onboard End Of Line (EOL) switch with LED indication provides easy EOL configuration and visual verification
- Remote addressing and software selectable inputs allow detailed configuration to be completed over the network
- Robust MRAM non-volatile memory preserves trend data on power cycle
- BACnet COV support provides optimized network sharing

Control-BASIC Programs

- 8500 bytes programmable control strategy in a readable, BASIC-like language
- 3200 bytes per program

Inputs

- Universal ranges
- Soft-selectable 0–10 VDC, 4–20 mA, thermistor/dry contact

Outputs

- Universal ranges
- 0–12 VDC or TRIAC, model dependent

Variables

- Selectable standard and custom ranges, as well as fixed or program-driven values

PID Loops

- Standard P, PI, or PID controllers for closed loop control

Velocity Sensor

- ± 0 –500 Pa (0–2" WC)
- Maximum zero point accuracy 0.2 Pa (0.0008" WC)
- Resolution: 0.133 Pa (0.0005" WC)
- Span accuracy 3% of reading

Actuator

- Torque 45 in-lb (5 Nm)
- Brushless D.C.

Enclosure

- ABS
- UL94-5V

Single-point Trend Logs

- Samples created at polled, COV, or triggered intervals
- Default 128 samples, configurable to allow trending over a longer period of time

Multipoint Trend Logs

- Each Trend Log includes 8 points at polled or triggered intervals
- Default 128 samples, configurable to allow trending over a longer period of time

Runtime Report

- Records the total On time and the total number of transitions, as well as daily transitions for every binary point
- A 50-sample runtime log is optional for each binary point

System Groups

- Allow related points to be grouped onto one display
- 80 points/group

Schedules

- 7 On/Off times for each weekday or exception

Calendars

- Days of the year designated as holidays

Arrays

- Up to 128 elements in a one-dimensional array

Tables

- For creating custom input ranges and Control-BASIC lookup tables

Custom Units

- 8 analog engineering units
- 8 binary engineering units
- 8 multistate units with 8 states, 32 characters each

SMART-Net™ Port

- Networks up to 4 SMART-Sensors™

32 Network In Points

16 Network Out Points

- The total maximum number of writes and shares to other devices

Warranty

- 5 years

Certification

- BTL Listed (B-BC)
- UL916 Listed (Pending)
- CE (Pending)

ORDERING

MPA-12-A-F

- MACH-ProAir™ with 1 universal input, 2 TRIAC outputs, actuator, and flow sensor

MPA-12-F

- MACH-ProAir™ with 1 universal input, 2 TRIAC outputs, and flow sensor

MPA-33-A

- MACH-ProAir™ with 3 universal inputs, 3 universal outputs, and actuator

MPA-33-A-F

- MACH-ProAir™ with 3 universal inputs, 3 universal outputs, actuator, and flow sensor

MPA-34-A

- MACH-ProAir™ with 3 universal inputs, 1 universal output, 3 TRIAC outputs, and actuator

MPA-34-A-F

- MACH-ProAir™ with 3 universal inputs, 1 universal output, 3 TRIAC outputs, actuator, and flow sensor

MPA-35-F

- MACH-ProAir™ with 3 universal inputs, 3 universal outputs, 2 TRIAC outputs, and flow sensor

MPA-36-F

- MACH-ProAir™ with 3 universal inputs, 1 universal output, 5 TRIAC outputs, and flow sensor

ACCESSORIES

LM24E5 RCC

- Replacement actuator - must be installed by Reliable Controls® service department

MPA-C

- Cover for wiring terminals



MPA-33-A-F with MPA-C

There are physical limitations to the number of inputs, outputs, and SMART-Sensors that can be connected to a MACH-ProAir™. For other object types, there are no imposed limits for the maximum number of objects of a single type. The main constraint for created objects is onboard memory, however, the total number of objects that can be created (including inputs, outputs, and SMART-Sensors) is limited to 128. The table below details a typical database that fits in the memory module for any model.

* Tables and Runtime Logs are not counted in the 128 object limit. Inputs, outputs, and the device object are counted in the 128 object limit.
 ** Trends are configured to store 128 samples.
 *** All models accommodate a maximum of 4 SMART-Sensors.

APPLICATION

Inputs

Outputs

Outputs

24 VAC/VDC Power†

MS/TP

Flow Pickup

SMART-Sensor LCD

Reliable controls

MACH-ProAir™

ADVANCED VAV CONTROLLER

USE ONLY CONNECTING WIRE
CLASS 2, 30VAC, 300A max.
For single connections
use wire rated for at
least 75°C (167°F)

CAUTION:
To Reduce the Risk of Fire
or Electrical Shock, do
NOT interconnect the
Outputs of Different Class
2 Circuits.

ATTENTION:
Après le câblage des bornes
d'interconnexion ou de choc
électrique, les bornes
recouvreuses doivent être
clipsées après montage de
câbles.

24VAC
GND
MS/TP-Net
DATA
GND
+S
CLK

On/Off
EOL
Status

SMART-Net

CE LOW HIGH

Reliable controls

Port-2
CONVERTER

Network Status

PC Monitor Status

72.8°F

57.7°F

72.8°F

Reliable controls

MPA-19/12/12-TKB